

Built-in Spindle Motor achieving  
high performance machine tool spindle

---

# FANUC

## BUILT-IN SPINDLE MOTOR **B1-B** series




# Built-in Spindle Motor achieving high performance machine tool spindle

## **FANUC** BUILT-IN SPINDLE MOTOR **B $\dot{i}$ -B** series

### **FANUC** BUILT-IN SPINDLE MOTOR **B $\dot{i}$ I-B** series

#### Features

- **B $\dot{i}$ I-B** series offers high power up to high speed range and is suitable for every kind of machine tool spindle.
- Large torque at low speed and high power at high speed achieved by speed range control
- Suitable model available for every kind of machine tool spindle from a wide range of line-up
- High response, high precision, high efficiency and lower motor loss achieved by Spindle HRV Control
- Larger torque and higher power due to efficient heat radiation of stator resin mold (Option)
- Stator with or without cooling jacket selectable for stator resin mold
- Even larger torque and higher power with copper-bar rotor (Some models)
- Water cooling available in addition to conventional oil cooling
- S6 short-time rated output equal to S3 available due to FANUC original spindle control



### **FANUC** BUILT-IN SPINDLE MOTOR **B $\dot{i}$ S-B** series

#### Features

- **B $\dot{i}$ S-B** series has two types of motor: IPM type (interior magnet) is suitable for turning with large torque at low speed and SPM type (surface magnet) is suitable for milling with high speed rotation.
- Compact size and large torque achieved with strong neodymium magnets
- Low torque ripple achieved by optimizing magnetic circuit design
- High speed and high power achieved by using Sub Module SM
- Larger torque and higher power due to efficient heat radiation of stator resin mold
- Stator with or without cooling jacket selectable for stator resin mold
- Water cooling available in addition to conventional oil cooling



## System configuration

### FANUC SERVO AMPLIFIER

$\alpha i$ -B series/ $\beta i$ -B series




Sub Module SM  
(only  **$\beta i$ S-B** series)




### FANUC

### BUILT-IN SPINDLE MOTOR

**$\beta i$ I-B** series/ **$\beta i$ S-B** series




$\alpha i$ **BZ** SENSOR /  $\alpha i$ **ICZ** SENSOR




## Stator resin mold ( **$\beta i$ I-B** series : Option, **$\beta i$ S-B** series : Standard)

- Larger torque, higher power or lower temperature rise due to efficient heat radiation of stator resin mold (Necessary to increase chiller capacity)

[Example]



Continuous rated output




Temperature rise at the same output


## Output specification with water cooling

- Larger torque, higher power or lower temperature rise due to higher the heat removal with water cooling (Necessary to increase chiller capacity)

[Example]



Continuous rated output




Temperature rise at the same output

# Service & Support

## Worldwide Customer Service

Conforming to the spirit of "Service First", FANUC provides lifetime maintenance to its products for as long as they are used by customers, through more than 260 service locations supporting more than 100 countries and regions throughout the world.

## FANUC Global Service Network Over 260 Locations Worldwide



**Service First**

## FANUC ACADEMY

FANUC ACADEMY operates versatile training courses to develop skilled engineers effectively in several days.

Inquiries : 3580, Shibokusa, Oshino-mura,  
Minamitsuru-gun, Yamanashi,  
401-0597, JAPAN

Phone : (+81)555-84-6030

Fax : (+81)555-84-5540



## FANUC CORPORATION

### ● Overseas Affiliated Companies

FANUC America Corporation

FANUC Europe Corporation, S.A.

BEIJING-FANUC Mechatronics CO., LTD

KOREA FANUC CORPORATION

TAIWAN FANUC CORPORATION

FANUC INDIA PRIVATE LIMITED

Phone: (+1)248-377-7000

Phone: (+352)727777-1

Phone: (+86)10-6298-4726

Phone: (+82)55-278-1200

Phone: (+886)4-2359-0522

Phone: (+91)80-2852-0057

● Headquarters 3580, Shibokusa, Oshino-mura, Minamitsuru-gun  
Yamanashi, 401-0597, JAPAN

Phone: (+81)555-84-5555 <https://www.fanuc.co.jp/>

<https://www.fanucamerica.com/>

<https://www.fanuc.eu/>

<http://www.bj-fanuc.com.cn/>

<https://www.fkc.co.kr/>

<https://www.fanuctaiwan.com.tw/>

<https://www.fanucindia.com/>

• All specifications are subject to change without notice.  
• No part of this catalog may be reproduced in any form.  
• The products in this catalog are controlled based on Japan's "Foreign Exchange and Foreign Trade Law". The export from Japan may be subject to an export license by the government of Japan. Further, re-export to another country may be subject to the license of the government of the country from where the product is re-exported. Furthermore, the product may also be controlled by re-export regulations of the United States government. Should you wish to export or re-export these products, please contact FANUC for advice.

© FANUC CORPORATION, 2005

Built-in SP B1-B(E)-07b, 2022.9, Printed in Japan